

LED Bollard (DB30) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:

Proposed FCO lighting LED site lighting throughout. Locations to be determined on site.



Ordering Guide

Example: DB30 A A0 12L E

Product Code	DB30	LED Bollard
Finish	A H	Black Bronze
Optics	A0	Symmetric
Wattage	12L	9.5W LED
Voltage	E	120V

Specifications

HOUSING:
360 low-copper die-cast aluminum alloy . Dome roof with die-cast aluminum louvers. Easy access to lamp. 5" dia. extruded aluminum with a wall thickness of 0.125". All non-ferrous fasteners prevent corrosion and ensure longer life.

FINISH:
Thermoset polyester powdercoat is electrostatically applied after a five-stage conversion cleaning process and bonded by heat fusion thermosetting. Laboratory tested for superior weatherability and fade resistance in accordance with ASTM B117 specifications. For larger projects where a custom color is required, contact the factory for more information.

OPTICAL ASSEMBLY:
Symmetric. Die-cast aluminum louvers with underside painted with highly reflective white powdercoat. Tempered glass globe.

LAMPING:
9.5W Philips LED EnduraLED lamp, LED 4Kv medium base porcelain socket A19. 2700K warm white delivers 800 lumens. Lamp life is rated at 25,000 hours. 120 volt only.

ELECTRICAL ASSEMBLY:
Ballast assembly is mounted to an aluminum plate, which is mounted inside the base. Quick disconnects for easy installation and removal.

INSTALLATION & MOUNTING:
Tube is mounted to the base plate with three (3) 5/16-18 flat head allen key stainless steel tamper-resistant screws.

WARRANTY:
Five-year limited warranty.

CERTIFICATIONS:
ETL listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards.

Height :
31 3/4" (80.65cm)

Width:
6" (15cm)

Bolt Circle:
3" (8 cm)

Anchor Rods:
Internal (3) 3/8" dia. x 8" long (1 cm x 20cm)

Base Diameter:
5" (13cm)

Max. Weight:
Powdercoat: 15 lbs